





## STORM-X

ENGINE	125 ABS-CBS	150 ABS
Engine type	Single-cylinder, 4-stroke, EU5	Single-cylinder, 4-stroke, EU5
Cooling	Air / Liquid	Liquid
Displacement	125 cc	150 cc
Maximum power	6.5 kW (9 hp) / 8.0 kW (11 hp)	10.5 kW (14.30 hp)
Engine distribution	SOHC 2-valve	SOHC 2-valve
Ignition system	Electronic managed by ECU	Electronic managed by ECU
Fuel management system	TARO electronic injection	TARO electronic injection
Starter system	Electric	Electric
Fuel tank capacity	10.5 ± 0.2 L	10.5 ± 0.2 L
TRANSMISSION		
Gearbox	Continuous variator	Continuous variator
Clutch	Automatic centrifugal	Automatic centrifugal
CHASSIS		
Туре	Multitubular steel chassis	Multitubular steel chassis
CUCDENCION SYSTEM		
Front	Hydraulic telescopic fork 31 mm Ø	Hydraulic telescopic fork 31 mm Ø
	Double hydraulic shock absorber	Double hydraulic shock absorber
Rear	adjustable in three positions	adjustable in three positions
BRAKING SYSTEM		
Braking system	ABS/CBS	ABS
Front brake	Disc 240 mm Ø	Disc 240 ABS mm Ø
Rear brake	Disc 220 mm Ø	Disc 220 mm Ø
DIMENSIONS		
Overall length	1.995 mm	1.995 mm
Overall width	770 mm	770 mm
Overall height	1.140 mm	1.140 mm
Wheelbase	1.360 mm	1.360 mm
Seat height	750 mm	750 mm
Wet weight	136 / 142 kg	142 kg
TYRE		
Front	110 / 70 - 14	110 / 70 - 14
Rear	130 / 70 - 13	130 / 70 - 13











■ FULL LED lighting



■ Double rear handlebars for increased passenger safety



■ Digital TFT colour dashboard with 5 levels of brightness (STORM-X+ & STORM-X 150)



■ Smartkey System (STORM-X+ & STORM-X 150)



■ Central opening under-seat compartment



Storage compartment to carry everything you need!







